

Aalto® Aluminium

Surface Mounted 10 x 75mm

PRODUCT SECTION — 1:1 (MM)



SPECIFICATION

Material	T6 tempered 6063 aluminium, anodised
Slip resistance	P5 (wet pendulum) to AS 4586
Luminance contrast	Requirement 30% (AS 1428.1)
Fire	Aluminium / brass — considered non-combustible; no fire test required (metals are deemed non-combustible under AS 1530.1).
Substrates	Stone / ceramic / concrete / masonry / timber / vinyl
Warranty	10 years
Variants	Surface Mounted 10x75mm · Recessed 10x61x5mm · Recessed 5x55mm
Product codes	211111 / 211114 / 211118 / 211121

Drawing: Aalto Aluminium Surface Mounted 10 x 75mm — product section | **Scale:** 1:1 | **Units:** mm | **Rev:** A | **Issued:** 2026-06-13
Dimensions per Korb PDS (2026). Editable CAD file supplied: **Aalto_Aluminium_Section.dxf** (opens in AutoCAD / Revit / ArchiCAD). Profile radii indicative; stated dimensions exact. Fix strictly to Korb installation instructions.

National (Head Office)

T 1300 00 KORB (5672)
E info@korb.au

Melbourne

17 Anderson Road,
Thornbury VIC 3071
T +61 3 8506 01
E melbourne@korb.au

Adelaide

71 Maria Street, Thebarton
SA 5031
T +61 8 7081 9811
E adelaide@korb.au

Perth

U4/4 McNeece Place,
O'Connor WA 6163
T +61 8 6119 3795
E perth@korb.au

Korb Pty Ltd

ABN 26 159 533 454