# Coral® Flooring Brush

## Entry Matting

Coral Flooring Brush Entry Matting is a brush-type textile entrance matting system, constructed with monofilament bristle fibres that scrape grit and absorb moisture from footwear at building entries. It is classified P5 to AS 4586, the highest wet-pendulum slip-resistance rating, and is durable under sustained foot traffic. Suited to high-traffic entrances where progressive removal of debris and surface water is required

**COMPLIES WITH** AS 4586 (slip resistance) · Critical Radiant Flux · Smoke Development Rate

### PRODUCT — CARRIER & MATTING FINISHES

### MATTING COLOUR




| P5 | 10.4 kW/m² | 10 yr | 2000mm |
|---|---|---|---|
| Wet pendulum slip (AS 4586) | Critical Radiant Flux | Product warranty | Roll width |

### SPECIFICATION

| | |
|---|---|
| **Critical Radiant Flux** | 10.4 kW/m² |
| **Smoke Development Rate** | 102% min |
| **Roll Width** | 2000mm |
| **Slip Resistance Classification** | P5 |
| **Warranty** | 10 years |

### MATTING COLOURS & LUMINANCE (LRV)

| MATTING COLOUR | CODE | MEAN DRY LUMINANCE (LRV) |
|---|---|---|
| Asphalt Grey | 340112 | 2 |
| Shark Grey | 340115 | 4 |
| Hurricane Grey | 340223 | 3 |
| Masala Brown | 340114 | 5 |
| Vulcan Black | 340111 | 1 |
| Chocolate Brown | 340116 | To be tested |

### SPECIFY IT

Specify: Korb Coral Flooring Brush Entry Matting; slip resistance P5 to AS 4586; 2000mm roll width; fixed to manufacturer's instructions. No substitution without written approval

Independently slip-tested to AS 4586 by ATTAR — NATA-accredited laboratory (Accreditation No. 2735) · Report 7457.3.

**National (Head Office)**
T 1300 00 KORB (5672)
E info@korb.au

**Melbourne**
17 Anderson Road,
Thornbury VIC 3071

**Adelaide**
71 Maria Street, Thebarton
SA 5031

**Perth**
U4/4 McNeece Place,
O'Connor WA 6163

**Korb Pty Ltd**
ABN 26 159 533 454