Kahn® Solid Carved

Integrated

The Kahn Solid Carved Integrated is an integrated TGSI: a carved granite stone paver with tactile indicators formed into the unit, available in ivory and black granite. The granite surface achieves a P5 slip-resistance classification to AS 4586, and tactile dimensions conform to AS 1428.4.1. Supplied to suit 20mm and 40mm paved areas; pair tones to meet the luminance contrast required under AS 1428.1

COMPLIES WITH AS 1428.4.1 (tactile dimensions) · AS 4586 (slip resistance) · AS 1428.1 (luminance contrast)

PRODUCT



PROFILE & DIMENSIONS (MM)



P5	30%	10 yr	Granite
Wet pendulum slip (AS 4586)	Luminance contrast requirement (AS 1428.1)	Product warranty	Carved stone paver

SPECIFICATION

Material	Carved granite stone paver
Profile	Integrated (Warning discrete domes + Directional bars)
Tactile colour	Black | Ivory
Slip resistance	P5
Luminance contrast requirement	30%
Paver depth	20mm or 40mm
Substrates	Stone | Ceramic | Asphalt
Warranty	10 Years

PRODUCT CODES & LUMINANCE (LRV)

TYPE	TACTILE COLOUR	20MM CODE	40MM CODE	DRY LRV	WET LRV
■ Integrated Warning	Black	132111	132211	12.44	6.97
□ Integrated Warning	Ivory	132114	132214	40.55	25.00
■ Integrated Directional	Black	132121	132221	12.44	6.97
□ Integrated Directional	Ivory	132124	132224	40.55	25.00

SPECIFY IT

Specify: Korb Kahn Solid Carved Integrated TGSI; carved granite stone paver (20mm or 40mm); slip resistance P5 to AS 4586; luminance contrast ≥30% to AS 1428.1; fixed to manufacturer's instructions. No substitution without written approval

Conforms to AS 4586 (slip resistance) · AS 1428.1 (luminance contrast) · TDS-TGSI-KAHN_SOLID_CARVED_INTEGRATED

Independently slip-tested to AS 4586 by ATTAR — NATA-accredited laboratory (Accreditation No. 2735) · Report 23640.1 / 23640.2.

National (Head Office)
T 1300 00 KORB (5672)
E info@korb.au

Melbourne
17 Anderson Road,
Thornbury VIC 3071

Adelaide
71 Maria Street, Thebarton
SA 5031

Perth
U4/4 McNeece Place,
O'Connor WA 6163

Korb Pty Ltd
ABN 26 159 533 454