Kahn® Modular

Discrete


The Kahn Modular Discrete is a discrete-type modular tactile ground surface indicator (TGSI) paver manufactured from granite and bluestone, with TGSI dimensions to AS 1428.4.1. It achieves a P5 slip resistance classification to AS 4586 and is available in ivory and black granite to meet the luminance contrast requirements of AS 1428.1. Other profiles are available within the Kahn Modular range


COMPLIES WITH AS 1428.4.1 (tactile dimensions) · AS 4586 (slip resistance) · AS 1428.1 (luminance contrast)

PRODUCT



PROFILE & DIMENSIONS (MM)





P5	45%	10 yr	Granite
Wet pendulum slip (AS 4586)	Luminance contrast requirement (AS 1428.1)	Product warranty	Bluestone paver

SPECIFICATION

Material	Granite and bluestone paver
Tactile Colour	Ivory
Tile Colour	Bluestone
Thickness	40 mm
Tile size	295 x 295 mm
Slip resistance	P5
Luminance contrast requirement	45%
Substrates	Stone | Ceramic | Asphalt
Warranty	10 Years

VARIANTS & LUMINANCE (LRV)

VARIANT	CODE	TACTILE COLOUR	TILE COLOUR	DRY LRV	WET LRV
Discrete Warning	131214	Ivory	Bluestone	40.55	25.00
Discrete Directional	131224	Ivory	Bluestone	40.55	25.00

SPECIFY IT

Specify: Korb Kahn Modular Discrete TGSI paver; granite and bluestone, ivory tactile on bluestone tile, 295 x 295 x 40 mm; slip resistance P5 to AS 4586; luminance contrast to AS 1428.1 (45% requirement); fixed to manufacturer's instructions. No substitution without written approval

Conforms to AS 4586 (slip resistance) · AS 1428.1 (luminance contrast) · TDS-TGSI-KAHN_MODULAR_DISCRETE
Independently slip-tested to AS 4586 by ATTAR — NATA-accredited laboratory (Accreditation No. 2735) · Report 23640.1 / 23640.2.

National (Head Office)
T 1300 00 KORB (5672)
E info@korb.au

Melbourne
17 Anderson Road,
Thornbury VIC 3071

Adelaide
71 Maria Street, Thebarton
SA 5031

Perth
U4/4 McNeece Place,
O'Connor WA 6163

Korb Pty Ltd
ABN 26 159 533 454