# TGSI, Stair Nosing & Entry Matting Schedule

To be read with the architectural drawings, specification and Korb product data sheets.

| PROJECT | PROJECT NO. | DOCUMENT NO. | REVISION | STATUS | ISSUE DATE | ARCHITECT | SUPPLIER |
|---|---|---|---|---|---|---|---|
| | | | | | 03/11/2026 | | Korb Pty Ltd · 1300 00 KORB (5672) |

**GENERAL NOTES**

1. Korb products are specified by name for luminance contrast, slip resistance and compliance. **No substitution** without the Architect's prior written approval, supported by current independent luminance contrast (AS/NZS 1428.4.1) and slip resistance (AS 4586) test reports for the proposed product on this project's floor finishes.
2. Supply and installation by **Korb Pty Ltd or a Korb-accredited installer only**.
3. **Luminance contrast to be confirmed by Korb**: on-site luminance contrast test of the installed product against the adjacent surface, wet and dry, with a Korb test certificate issued at completion.
4. Read with the drawings, specification and Korb data sheets. Refer to plans for exact locations; dimensions to be verified on site.

| CODE | ITEM | LOCATION | PRODUCT SELECTION | NOTES | SUPPLIER | IMAGE | REV |
|---|---|---|---|---|---|---|---|
| **TACTILE GROUND SURFACE INDICATORS (TGS)** | | | | | | | |
| **TGS-01** | Discrete warning TGSIs | LRV not entered<br>Refer to plans for exact locations. | Manufacturer: Korb<br>Range: Kahn Modular Discrete Warning<br>Code: 131214<br>Material / finish: Ivory granite / Bluestone<br>Size: 295 x 295 x 40 mm<br>LRV (dry / wet): 40.55 / 25 (LRV shown is for the ivory granite tactile. The data sheet gives no LRV for the bluestone tile)<br>Slip rating: P5 (AS 4586)<br>Luminance contrast: Minimum 45% to adjacent floor, wet and dry (AS/NZS 1428.4.1)<br>Data sheet · Product page | **Installed by Korb or a Korb-accredited installer only.**<br>**Luminance contrast to be confirmed by Korb on-site test at completion; certificate to Architect.**<br>WARRANTY: 10-year Korb manufacturer's warranty; installation workmanship covered when installed by Korb or a Korb-accredited installer. | Korb Pty Ltd<br>1300 00 KORB (5672)<br>info@korb.au<br>korb.au |  | |

SPECIFICATION CLAUSE

# TACTILE GROUND SURFACE INDICATORS

**Product:** Kahn® Modular by Korb Pty Ltd
**Type:** Modular granite and bluestone discrete tactile indicator paver
**Material:** Ivory granite tactile on bluestone paver
**Format:** 295mm x 295mm x 40mm
**Configuration:** warning and directional as required
**Application:** as specified by architect

### PERFORMANCE REQUIREMENT (any supplied product must meet)

- Luminance contrast: minimum 45% to the adjacent surface, required to AS 1428.1 (TGSI luminance contrast determined per AS 1428.4.1:2009).
- Compliance: AS 1428.4.1:2009 · AS 1428.1:2021 · AS 4586:2013 · NCC 2022 Part D4 (D4D9).

### ADDITIONALLY

- Slip resistance: classified P5 to AS 4586:2013.
- Measured luminance-contrast / slip-resistance test reports available on request.

### INSTALLED BY

Supplied and installed by Korb Pty Ltd's qualified installers (VIC · SA · WA).

### WARRANTY

10 year manufacturer's warranty against defects in materials and workmanship.

### SUPPLIER

Korb Pty Ltd
www.korb.au | info@korb.au
VIC · SA · WA

### SUBSTITUTION

This item is specified as Kahn® Modular by Korb Pty Ltd. Where documented "or equal approved", any proposed substitute must demonstrably satisfy EVERY stated minimum above: luminance contrast %, slip classification and format dimensions, verified by current test reports. Kahn® Modular meets or exceeds all stated requirements.

Clause generated by korb.au/spec-tools on 03/11/2026. References AS standards current at this date. Verify currency before final submission.