# TGSI, Stair Nosing & Entry Matting Schedule

To be read with the architectural drawings, specification and Korb product data sheets.

| PROJECT | PROJECT NO. | DOCUMENT NO. | REVISION | STATUS | ISSUE DATE | ARCHITECT | SUPPLIER |
|---|---|---|---|---|---|---|---|
| | | | | | 03/11/2026 | | Korb Pty Ltd · 1300 00 KORB (5672) |

**GENERAL NOTES**

1. Korb products are specified by name for luminance contrast, slip resistance and compliance. **No substitution** without the Architect's prior written approval, supported by current independent luminance contrast (AS/NZS 1428.4.1) and slip resistance (AS 4586) test reports for the proposed product on this project's floor finishes.
2. Supply and installation by **Korb Pty Ltd or a Korb-accredited installer only**.
3. **Luminance contrast to be confirmed by Korb**: on-site luminance contrast test of the installed product against the adjacent surface, wet and dry, with a Korb test certificate issued at completion.
4. Read with the drawings, specification and Korb data sheets. Refer to plans for exact locations; dimensions to be verified on site.

| CODE | ITEM | LOCATION | PRODUCT SELECTION | NOTES | SUPPLIER | IMAGE | REV |
|---|---|---|---|---|---|---|---|
| **ENTRY MATTING (MAT)** | | | | | | | |
| **MAT-01** | Entry matting | LRV not entered<br>Refer to plans for exact locations. | Manufacturer: Korb<br>Range: Rohre Aluminium Coral Brush<br>Code: TBC (contact Korb)<br>Material / finish: Anodised Aluminium carrier (Mill/Black/Heritage/Champagne) with high-retention brush insert<br>Size: 600 mm tile, 13 mm high<br>Slip rating: P5 (AS 4586)<br>Data sheet · Product page | **Installed by Korb or a Korb-accredited installer only.**<br>WARRANTY: 10-year Korb manufacturer's warranty; installation workmanship covered when installed by Korb or a Korb-accredited installer. | Korb Pty Ltd<br>1300 00 KORB (5672)<br>info@korb.au<br>korb.au |  | |

SPECIFICATION CLAUSE

# ENTRANCE MATTING

**Product:** Rohre® Aluminium Brush by Korb Pty Ltd
**Type:** Recessed entrance matting system - brush insert
**Material:** Anodised Aluminium carrier (Mill/Black/Heritage/Champagne) with high-retention brush insert
**Format:** Modular panels, cut to mat well dimensions
**Zone:** Zone 2/3 primary entry and circulation
**Application:** as specified by architect

### PERFORMANCE REQUIREMENT (attribute-led)

- Installation: recessed mat well (or surface-mounted framing where noted).
- Coverage: full doorway width, minimum 1 metre depth of foot travel (greater depth removes more dirt and moisture, so specify to suit traffic).
- Carrier: anodised aluminium (Mill/Black/Heritage/Champagne).
- Insert: high-retention scraper brush, retains dirt and moisture at entry.
- Slip resistance: classified P5 to AS 4586:2013.
- Compliance: AS 4586:2013.

### INSTALLED BY

Supplied and installed by Korb Pty Ltd’s qualified installers (VIC · SA · WA).

### WARRANTY

10 year manufacturer’s warranty against defects in materials and workmanship.

### SUPPLIER

Korb Pty Ltd
www.korb.au | info@korb.au
VIC · SA · WA

### SUBSTITUTION

This item is specified as Rohre® Aluminium Brush by Korb Pty Ltd. Where documented "or equal approved", any proposed substitute must demonstrably satisfy EVERY stated minimum above: recessed-well depth, coverage width, carrier material/finish and insert retention, verified by current test reports. Rohre® Aluminium Brush meets or exceeds all stated requirements.

Clause generated by korb.au/spec-tools on 03/11/2026. References AS standards current at this date. Verify currency before final submission.