
# TGSI, Stair Nosing & Entry Matting Schedule

To be read with the architectural drawings, specification and Korb product data sheets.

| PROJECT | PROJECT NO. | DOCUMENT NO. | REVISION | STATUS | ISSUE DATE | ARCHITECT | SUPPLIER |
|---|---|---|---|---|---|---|---|
| | | | | | 03/11/2026 | | Korb Pty Ltd · 1300 00 KORB (5672) |

**GENERAL NOTES**

1. Korb products are specified by name for luminance contrast, slip resistance and compliance. **No substitution** without the Architect's prior written approval, supported by current independent luminance contrast (AS/NZS 1428.4.1) and slip resistance (AS 4586) test reports for the proposed product on this project's floor finishes.
2. Supply and installation by **Korb Pty Ltd or a Korb-accredited installer only**.
3. **Luminance contrast to be confirmed by Korb**: on-site luminance contrast test of the installed product against the adjacent surface, wet and dry, with a Korb test certificate issued at completion.
4. Read with the drawings, specification and Korb data sheets. Refer to plans for exact locations; dimensions to be verified on site.

| CODE | ITEM | LOCATION | PRODUCT SELECTION | NOTES | SUPPLIER | IMAGE | REV |
|---|---|---|---|---|---|---|---|
| **STAIR NOSINGS (NOS)** | | | | | | | |
| **NOS-01** | Stair nosing | LRV not entered<br>Refer to plans for exact locations. | Manufacturer: Korb<br>Range: Tadao Aluminium Striped 50 x 3<br>Code: TBC (contact Korb)<br>Material / finish: Anodised Aluminium 6063 T6 - Striped<br>Size: 50 x 3 mm<br>Insert LRV (dry / wet): TBC / TBC<br>Slip rating: P4 (AS 4586)<br>Luminance contrast: Minimum 30% to adjacent tread, wet and dry (AS 1428.1)<br>Data sheet · Product page | **Installed by Korb or a Korb-accredited installer only.**<br>**Luminance contrast to be confirmed by Korb on-site test at completion; certificate to Architect.**<br>WARRANTY: 5-year Korb manufacturer's warranty; installation workmanship covered when installed by Korb or a Korb-accredited installer. | Korb Pty Ltd<br>1300 00 KORB (5672)<br>info@korb.au<br>korb.au |  | |

SPECIFICATION CLAUSE

# STAIR NOSING

**Product:** Tadao® Aluminium 50 x 3mm by Korb Pty Ltd
**Type:** Anodised aluminium 6063 T6 stair nosing with corrugated or striped tread face
**Material:** Anodised Aluminium 6063 T6 - Striped
**Format:** 50mm wide x 3mm flat strip, no nosing leg. Continuous length, custom cut to stair width
**Configuration:** Flat strip, corrugated or striped as required
**Application:** as specified by architect

### PERFORMANCE REQUIREMENT (any supplied product must meet)

- Luminance contrast: minimum 30% to the adjacent tread and riser, required to AS 1428.1.
- Contrast strip: 50 to 75mm on the tread. Where the strip is not set back from the front of the nosing, contrast must not extend down the riser more than 10mm. The strip may be set back a maximum of 15mm (AS 1428.1).
- Slip resistance: classified P4 to AS 4586:2013. The corrugated or striped tread face carries the slip resistance and the nosing itself is the contrasting luminance band.
- Compliance: AS 1428.1:2021 · AS 4586:2013 · NCC 2022 Part D3.

### INSTALLATION

- Fixing method: surface mounted to the finished tread, or recessed in a routed rebate, recommended rebate 52 x 4mm (W x D), per the architect's stair detail.
- Fixing: Adhesive fixed.

### INSTALLED BY

Supplied and installed by Korb Pty Ltd's qualified installers (VIC · SA · WA).

### WARRANTY

5 year manufacturer's warranty against defects in materials and workmanship.

### SUPPLIER

Korb Pty Ltd
www.korb.au | info@korb.au
VIC · SA · WA

### SUBSTITUTION

This item is specified as Tadao® Aluminium 50 x 3mm by Korb Pty Ltd. Where documented "or equal approved", any proposed substitute must demonstrably satisfy EVERY stated minimum above: luminance contrast %, slip classification, strip/format dimensions and installation method, verified by current test reports. Tadao® Aluminium 50 x 3mm meets or exceeds all stated requirements.

Clause generated by korb.au/spec-tools on 03/11/2026. References AS standards current at this date. Verify currency before final submission.